

# KS21 SUBWOOFER



- High power compact 21" subwoofer
- Exceptional impact
- Augmented short-term SPL
- Lightweight (49 kg / 108 lbs)
- Simple, fast, integral rigging
- Supported by LA4X and LA12X



## ELECTRO-ACOUSTICS



KS21 is a compact reference subwoofer designed to extend the bandwidth of A15 and A10 systems. KS21 features one high excursion, direct radiating 21" transducer mounted in a bass-reflex tuned enclosure.


KS21 couples with A15 and A10 to reinforce contour and extend bandwidth to 29 Hz and 31 Hz respectively. KS21 features L-Vents that substantially reduce turbulence and port noise at high levels while also increasing LF efficiency. The association of modern components and laminar vents greatly improves short-term SPL compared to similar-sized subwoofers.

The KS21 frequency response is optimized to couple perfectly with both systems. KS21 features a two-point, integrated rigging system that is compatible with A15. Combinations of KS21 and A15 can be flown or stacked to form a full range line source. KS21 also integrates a threaded insert to enable pole-mount configurations of A15 or A10.

KS21 can be deployed in standard or cardioid configurations with dedicated presets, for flown and stacked deployment.



L-Vents laminar vented ports




Rear SPL rejection (cardioid)

## PHYSICAL

The KS21 enclosure is constructed of premium grade Baltic beech and birch plywood to ensure maximum acoustical and mechanical integrity. Bent wood technology combined with a thickness optimization process maximizes internal volume while attaining the low weight of 49 kg / 108 lb. The lightweight and robust design facilitates deployment and on-the-road manipulation.

KS21 integrates a patent pending two-point, captive rigging system that simplifies deployment and provides visual safety assessment. KS21 features ergonomic handles to ensure efficient handling, bottom ground runners and matching top tracks to secure stacking deployment and corner stops to protect side panels.


KS21 has been weatherized to achieve an IP55 rating for outdoor operations.




Integrated rigging with safety check; ergonomic handles; ground runners; corner stops.

## APPLICATIONS AND BENEFITS

KS21 is the ideal companion for small to large events that require bandwidth extension and strong impact in a compact enclosure. KS21 is acoustically compatible with A15 and A10 and therefore is particularly suited to reinforce the low frequency contour of both systems.






Corporate main system



Green field main system

## RIGGING

KS21 can be groundstacked horizontally or stacked vertically on a KS21-CHARIOT. A15-BUMP supports flown vertical arrays in standard or cardioid arrangements. KS21 integrates a secure and easy-to-use rigging system that is compatible with A15 to facilitate any combination of flown or stacked deployment.

 <p><b>Groundstacked / KS21-CHARIOT</b> Up to 3 KS21 per KS21-CHARIOT</p>	 <p><b>A15-BUMP</b> Up to 16 KS21</p>	 <p><b>A15-RIGBAR</b> Up to 4 KS21</p>

## TRANSPORTATION ACCESSORIES


<p><b>KS21-COV</b> protective cover for 1 KS21</p>	<p><b>KS21-PLA</b> removable front dolly for 1 KS21</p>	<p><b>KS21-CHARIOTCOV</b> protective cover for 3 or 2 KS21 on KS21-CHARIOT</p>	<p><b>KS21-CHARIOT</b> chariot for up to 3 KS21</p>
			

# AMPLIFIED CONTROLLER

## LA4X: amplified controller with DSP




4 x 1000 W / 8 ohms or 4 ohms  
 4 inputs x 4 outputs architecture  
 Max 4 enclosures per amplified controller



## LA12X: amplified controller with DSP



4 x 2600 W / 4 ohms  
 4 inputs x 4 outputs architecture  
 Max 8 enclosures per amplified controller



# ASSOCIATED ENCLOSURES

A SERIES




X SERIES



# SOFTWARE

## SOUNDVISION: simulation software



3D electro-acoustic & mechanical simulation software

## LA Network Manager: control & monitoring software



Real-time control and monitoring up to 253 units  
 Multiple network topologies



SB15m



SB18 (i/m)



KS21



K1-SB



SB28



KS28

## Subwoofers: a complete range for professional sound reinforcement

L-Acoustics subwoofers complement systems in applications where extended bandwidth is required.

All subs incorporate high excursion drivers, ultra-low vibration walls and laminar airflow L-Vents with a flared profile, resulting in dramatic reduction of port noise, maximized dynamics, power handling and an exceptional level of performance.

# KS21 SUBWOOFER





<b>Description</b>	High power compact subwoofer: 1 x 21" amplified by LA4X / LA8 / LA12X
<b>Low frequency limit (-10 dB)</b>	29 Hz ([KS21_60])
<b>Maximum SPL<sup>1</sup></b>	138 dB ([KS21_100])
<b>Nominal directivity</b>	Standard or cardioid configurations
<b>Transducers</b>	1 x 21" neodymium cone driver
<b>Acoustical load</b>	Bass-reflex, L-Vents
<b>Nominal impedance</b>	8 Ω
<b>Connectors</b>	IN: 1 x 4-point speakON LINK: 1 x 4-point speakON
<b>Rigging and handling</b>	Flush-fitting two-point rigging system 1 pole mount with M20 x 150 insert 4 handles, 8 corner stops and 2 ground runners
<b>Weight (net)</b>	49 kg / 108 lb
<b>Cabinet</b>	Premium grade Baltic beech and birch plywood
<b>Front</b>	Coated steel grill Acoustically neutral 3D fabric
<b>Rigging components</b>	High grade steel with anti-corrosion coating
<b>Finish</b>	Dark grey brown Pantone 426 C
<b>IP</b>	IP55




<sup>1</sup> Peak level at 1 m under half space conditions using pink noise with crest factor 4 (preset specified in brackets).

## ISOCONTOUR




► SPL mapping of a block of four KS21 in standard (left) and cardioid (right) arrangements, using surfaces of equal sound pressure with three dB step colored scale.


## DIMENSIONS



Front



Side



Top