

showSTORE Xlan

Product ref: DSS Xlan

Real-time DMX and Ethernet recorder / player



The showSTORE Xlan is an advanced DMX playback recorder that can record and playback DMX data over Ethernet like a tape recorder. All DMX changes / fades / effects for all channels on up to 4 Ethernet Universes (2048 channels) are recorded for a maximum of 24 hours in real time using solid state nonvolatile flash memory, and can be played back accurately.

Up to 99 shows of lighting data may be recorded from either the Ethernet network and/or 2 DMX XLR5 input ports, and replayed via Ethernet and/or XLR outputs. The showSTORE Xlan is fully programmable and is compatible with ELC dmXlan software. It is ideal for automating stand-alone shows, such as retail and exhibition displays, including moving light effects.

Features include:

- Real-time recording of 4 DMX universes to replay up to 99 automated shows on a solid-state 4GB SD memory card with a capacity up to 24 hours

- Provides a stand-alone control system to replace a regular DMX console
- Built-in Ethernet-DMX node
- Comprehensive external triggering using single or combined elements including contact closures, MIDI, RS232, realtime clock (with 12-month calendar), TCP/Telnet commands, SMPTE timecode, ASCII command set, or DMX-In
- USB connection for file exchange and backup, compatible with PC and Mac
- FTP and internal webserver features

Dimensions	19" x 1U x 160mm, 5.6lbs [box size: 570 x 280 x 72mm, 6.5lbs gross]
Power	100-240VAC 50/60Hz, fixed mains lead
Connections	2 x 5-pin XLR (F) outputs, 2 x 5-pin XLR (M) inputs 1 x 10/100Mbit Ethernet connection (Neutrik Ethercon) MIDI-in, MIDI-out, USB 2.0 1/4" jack: SMPTE input 2 x Sub-D 9-pin: contact closures and RS232 for PC connection
Controls	Graphic LCD display, backlit. Rotary encoder and buttons A & B for menu feature navigation and selection, setup menu button. LED displays: Power on/LAN active/Recording in progress/Playback in progress. Power on/off
Options	ELC dmXLAN software (free download from www.elclighting.com) Connections options: 3-pin or 5-pin XLR to special order
Supplied	DSS Xlan, fitted mains cable, operator leaflet
Related products	DMS: miniSTORE 3 MkII, DMX show recorder/player 512 channels DMX on XLR 3 or 5