

th.mann



Facture-n° : 66403942

Thomann GmbH, Hans-Thomann-Str. 1, D-96138 Burgebrach

MX EVENEMENT
Mx Evenement
10 Rue De la Ferme Saint-Ladre

F-95470 Fosses

Adresse de livraison:

MX EVENEMENT
Mx Evenement
10 Rue De la Ferme Saint-Ladre

F-95470 Fosses

Facture-n° : 66403942

Date: 21.03.2023

Votre numéro client 7854402

Notre n° d'ordre: 202312.162660 / 2225

Vendeur: Maria Elena Terol Mendoza
Téléphone: 0049 9546 / 9223 640
Livraison par: UPS
Votre référence:

Votre numéro de TVA: FR78530672666
livraison intracommunautaire exonérée TVA

Indiquez s'il vous plaît votre numéro de client 7854402 lors du paiement!

N° pos.	Article	Quantité	Unité	Prix unit.	Total
001.00	532904	1	pce	48,33 EUR	48,33 EUR
	Showgear 19" 1U Socketstrip 7, Bloc multiprise à 7 contacts de protection 19" 1U, Raccordement électrique : entrée et sortie Power Twist à l'avant (câble de raccordement d'env. 2m compris dans la livraison), 7x prises à l'arrière avec mise à la terre, Dimensions (LxHxl) : 483 x 44 x 50 mm, Poids : 0,95 kg				
002.00	150527	34	pce	7,66 EUR	260,44 EUR
	Neutrik NBB 75 DFIB BNC Socket, Châssis BNC, 75 Ohm, Format D, Couleur: Noir				
				Montant reporté:	308,77 EUR

Thomann GmbH
Hans-Thomann-Str. 1
D-96138 Burgebrach

info@thomann.de
Tel +49 (0)9546 9223-66
Fax +49 (0)9546 9223-24

Geschäftsführer: Johann Thomann
Amtsgericht Bamberg: HRB 5862
Sitz der Gesellschaft: Burgebrach

USt-IdNr.: DE 257375233
Steuernummer: 207/132/90050
WEEE-Reg.-Nr.: DE 18280160

Bank Sparkasse Bamberg
IBAN DE97 7705 0000 0000 1030 85
BIC BYLADEM1SKB

Raiffeisenbank Burgebrach
DE58 7706 2014 0000 0056 30
GENODEF1BGB

Postbank Nürnberg
DE41 7601 0085 0283 5648 54
PBNKDEFF

Deutsche Bank 24
DE19 7607 0024 0811 5008 00
DEUTDEDB760

MUSIC IS OUR PASSION



Page 2 pour facture n°: 66403942 du 21.03.2023 pour Mx Evenement (N° client: 7854402)

N° pos.	Article	Quantité	Unité	Prix unit.	Total
003.00	525693	1	pce	629,17 EUR	629,17 EUR

Blackmagic Design HyperDeck Studio HD Plus; Broadcast deck for recording and playback of H.264- files up to 1080p/60 and ProRes or DNxHD files in SD/HD formats up to 2160p/30 to SD/UHS-II cards or external USB drives; Offers all the features of the mini model plus better transport control, front headphone jack and speakers, plus 6G-SDI and fill and key signal output; 6G-SDI inputs and outputs; HDMI In/Output; dual SD card slots allow card swapping on the fly; built-in clock and timecode generators; higher quality front panel controls; acts like a webcam when connected to a computer via USB port; can be used with any video software; connections: ; SDI video inputs: 1; SDI video outputs: 2; SDI monitor outputs: 1; SDI rates: 270 Mbit, 1.5 G, 3 G, 6 G; HDMI 2.0 video inputs: 1; HDMI 2.0 video outputs: 1; Timecode connections: 1 BNC input, 1 BNC output; Reference connections: 1 BNC input, 1 BNC output, Tri-Sync or Black Burst; SDI audio inputs & outputs: 16 embedded audio channels; HDMI audio outputs: 8 embedded audio channels; Remote control: 1 RS-422 input, 1 RS-422 output; Computer interface: 1 USB-C-3.0 (up to 5 Gb/s) for recording to external drives, webcam output, software configuration and updates; Standards;; Video sampling frequency: 4:2:2 YUV; Colour accuracy: 10 bit; Colour spaces: Rec. 601, Rec. 709, Rec. 2020. 33-point 3D LUTs can be applied to SDI monitor output; HDR support: Hybrid Log-Gamma, ST2084 300, ST2084 500, ST2084 800, ST2084 1000, ST2084 2000, ST2084 4000, ST2084; Multirate support:Auto detection of SD, HD and 6G-SDI; Media: 2 SD card slots, 1 USB-C 3.0 expansion port for external recording in SD, HD, 2K DCI, Ultra HD and 4K DCI; Media type: UHS-I and UHS-II SD cards; Storage media format: formats media in ExFAT (Windows/Mac) or HFS+ (Mac) file systems; Supported codecs: ; ProRes HQ QuickTime, ProRes 422 QuickTime, ProRes LT QuickTime, ProRes Proxy QuickTime in all formats up to 2160p/30 playback only in ProRes 4444 QuickTime up to 1080p/60; automatic distribution of fill-and-key signals via SDI outputs A and B DNxHD 220x, DNxHD 220x MFX, DNxHD 145, DNxHD 145 MXF, DNxHD 45, DNxHD 45 MXF in 720p and 1080p HD formats up to 60 fps DNxHR HQX, DNxHR HQX MXF, DNxHR SQ, DNxHR SQ MXF, DNxHR LB, DNxHR LB MXF in 2K DCI and 2160p formats up to 30 fps H. 264 SDI 4:2:2 10 bit, H.264 High 4:2:0 8 bit, H.264 Medium 4:2:0 8 bit,H.264 Low 4:2:0 8 bit in all formats up to 1080p/60; control;; integrated control panel: 13 buttons for transport and device control with seek slider and 2.2 inch colour display; external control: RS-422 deck control, SDI start/stop, timecode run. Blackmagic HyperDeck Ethernet Protocol included Supports remote file uploads via FTP; included software;; Blackmagic OS; Blackmagic HyperDeck Setup; product software upgrades loaded at boot-up or via Blackmagic HyperDeck Setup via USB port; compatible operating systems;; Mac Catalina 10.15, Mac Big Sur 11.1 or higher; Windows 10, 64 bit; Power supply;; 1 built-in AC power supply for 100 240 V, 50/60 Hz; 1 four-pin XLR socket for external 12V DC power supply or battery charging (power cable not included); Dimensions: 210 x 177 x 44.2 mm (1 height unit, half rack width); Weight: 1.15 kg; Note: Copy-protected HDMI sources cannot be recorded via the HDMI input. Always inform yourself about copyright before recording or distributing content

Valeur marchandise: **937,94 EUR**

Mode de paiement:

Paypal **937,94 EUR**

Merci pour vos achats!

Nos conditions générales indiquées au verso sont d'application.
Sauf indication contraire la date de facture correspond à la date de la prestation/livraison.