

# Pointe®

**It's very bright and super-fast with a sharp parallel beam that cuts through the air and across video with ease.**

It can project a static or rotating glass gobo to produce precision in-air and surface images with an even focal plane. Tight or at full 20 degree zoom, the output is crystal clear and brilliant. Add in either rotating, 6 way linear or 8 way circular, prisms to create wide reaching effects across any set. Drop in the frost filter and use any of the 13 rich colours to create a smooth even wash. The Pointe has an output far greater in size, quality and power than seems possible from it's small, lightweight body - due to the efficient short arc 280 W discharge source and the Robe optical configuration. This new technology fixture even travels efficiently in a case of 4 and will cover all your needs - Beam, Spot, Wash, FX - there is no point in using any other fixture.

**Light source**

Osram Sirius HRI 280W RO

**LIGHT OUTPUT**

Beam mode: 9.870 lm, 82.400 lx @ 20 m  
Spot mode: 5.150 lm, 90.000 lx @ 5 m

**Zoom range**

2, 5° - 10° Beam mode, 5° - 20° Spot mode

**Effects**

rotating and static gobo wheel, circular 8-facet and linear 6-facet prism

# Technical Specification

## SOURCE

- Lamp: Discharge short arc lamp with integrated reflector
- Approved model: Osram Sirius HRI 280 W RO
- Lamp Life Expectancy: Standard mode (280 W) - 2.000 hrs, Eco mode (230 W) - 3.000 hrs
- Control: Automatic and remote on/off
- Ballast: Electronic

## OPTICAL SYSTEM

### 1. Light Output:

- Beam mode: 82,400 lx @ 20 m distance
- Spot mode: 90,000 lx @ 5 m distance
- Dichroic glass reflector integrated with the lamp for maximising the light efficiency
- Zoom range: 2.5°-10° beam application; 5° - 20° spot application

## ELECTROMECHANICAL EFFECTS

- Colour wheel: 13 dichroic filters + white
- Rotating Gobo wheel: 9 rotating, indexable and replaceable "SLOT&LOCK" glass gobos + open
- Static Gobo wheel: 14 gobos + open
- Prism 1: 8-facet circular prism rotating in both directions at different speeds
- Prism 2: 6-facet linear prism rotating in both directions at different speeds
- Frost effect: Separate, variable
- Dimmer/Shutter: Full range dimming and variable strobe effect
- Motorized zoom and focus
- Pan: 540°
- Tilt: 270°

## CONTROL AND PROGRAMMING

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2
- Optional wireless version available: CRMX™ technology from Lumen Radio
- Control channels: 24, 16, 30
- 3 DMX protocol modes
- 3-editable programs, each up to 100 steps
- Stand-alone operation
- QVGA Robe touch screen with battery backup gravitation sensor for auto screen positioning operation memory service log with RTC
- Pan/Tilt resolution: 8 or 16 bit
- Movement control: Tracking and vector
- Colour wheel positioning: 8 or 16bit
- Rotating gobo wheel positioning: 8 bit
- Gobo indexing & rotation: 8 or 16bit
- Static gobo wheel positioning: 8 bitt
- Prism indexing & rotation: 8 bit

- Frost: 8 bit
- Zoom: 8 or 16bit
- Focus: 8 or 16bit
- Dimmer: 8 or 16bit
- Ethernet port: Art-Net, MA Net, MA Net 2 protocols, ready for ACN
- Data in/out: Locking 3-pin & 5-pin XLR
- Power input: Neutrik PowerCon
- Built-in analyser for easy fault finding

## ROTATING GOBOS

- Glass gobos - outside diameter: 15,9 mm, image diameter: 12,5 mm, thickness: 1.1 mm, high temperature borofloat or better glass

## STATIC - BEAM GOBOS

- Aluminium gobo wheel - thickness: 0,5 mm, gobo image diameter: 6 mm

## THERMAL SPECIFICATION

- Maximum ambient temperature: 45 °C (104 °F)
- Maximum surface temperature: 100 °C (212 °F)

## ELECTRICAL SPECIFICATION

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: 470 W at 230 V / 50 Hz



## MECHANICAL SPECIFICATION

- Height: 575 mm (22.6") - head in vertical position
- Width: 364 mm (14.3")
- Depth: 250 mm (9.8")
- Weight: 15 kg (33 lbs)
- Fixation option: Pan/Tilt-lock mechanism

## RIGGING

- Mounting points: 2 pairs of ¼-turn locks
- 2 x Omega bracket with ¼-turn quick locks
- 1 x Safety attachment point

## gobos & colours

### ROTATING GOBO WHEEL



15020276




15020277



15020278



15020279




15020280



15020281



15020282



15020283



15020284

### COLOUR WHEEL



14070356



14070357



14070358



14070359



14070360



14070368



14070361



14070362



14070363



14070364



14070365



14070366



14070367

### FIXED GOBO WHEEL



99013881